

Table of Contents

Specifications 1A-1

Propeller Information Charts 1A-7

Specifications

| Models 30/40 (4-Stroke) | | |
|-------------------------|--|--|
| HORSEPOWER (kW) | Model 30 Model 40 | 30 hp (22.4 Kw) @ 5750 rpm 40 hp (29.8 Kw) @ 5750 rpm |
| OUTBOARD WEIGHT | Electric 30/40 ELPT 40 ELPT BIGFOOT | 212 lb (96.2 kg) 235 lb (106.6 kg) |
| FUEL | RECOMMENDED GASOLINE | Automotive Unleaded with a Minimum Pump Posted Octane Rating of 87 |
| OIL | OIL FILTER OIL FILTER WRENCH ENGINE OIL CAPACITY ENGINE OIL | <p>p/n 35-822626A2 p/n 91-802653 Either 3 Quarts or 3 Liters SAE 10W-30 viscosity oil is recommended for use in all temperatures. SAE 25W-40 viscosity oil may be used at temperatures above 40° F (4° C).</p> <p>Use Quicksilver 4-Cycle Marine Oil with the proper viscosity for the expected temperature in your area (see range thermometer on left). If not available, use a premium quality 4-cycle engine oil, certified to meet or exceed anyone of the following American Petroleum Institute (API) service classifications SH, SG, SF, CF-4, CE, CD, CDII.</p> |

